

DUST & STATIC

4125 IONISED AIRGUN

The 4125 is our most powerful airgun for neutralising static electricity and removing dust and other contaminants.

It is available in two variants for top or bottom air feed.

- > The 4125 is suitable for the most demanding cleaning and static neutralising work.
- > The open construction of the ionisation head and the airflow amplifier nozzle give the 4125 operational efficiency, producing maximum ionisation with maximum airflow.
- > The hand trigger, in addition to being very robust and ergonomic, gives the operator excellent control of the airflow.
- > The air consumption is minimised by the air nozzle which amplifies the compressed air by 20:1.
- > Ergonomic full-hand trigger is suitable for all day use, unlike designs using one or two fingers.
- > The robust and modular design is designed for easy repair and maintenance designs using one or two fingers.



Specification

Construction:	Stainless steel ionisation head and guard, PTFE ionising head, plastic handle, Aluminium nozzle.
Operation:	Maximum air pressure 7 Bar. Recommended working pressure is 5 Bar. Air consumption at 5 Bar is 560 lit/min.
Cable:	Purpose designed Hi-Flex HT cable is flexible, light and very durable. Available in lengths of 3m, 5m, 7m and 10m.
Safety:	The ionisation system is shockless and meets OSHA and other Safety Standards. The nozzle cannot be dead-ended.
Noise	At 5 Bar noise level is 74 dBA. At 7 Bar it is 90dBA., measured at 1m.
Power Unit:	Use with Fraser 5.5kv or 6kV Power Units - see separate Datasheets
Thrust <small>(airspeed x volume which represents cleaning power)</small>	At 5 Bar the thrust at a distance of 100mm is 5.2N, nearly three times the thrust of the standard Gun.
Air Connections & Pipe	1/4 BSP threaded connection. Supply pipe should be at least 6mm internal diameter for full performance. If the pipe is long then a bigger bore may be needed to prevent pressure drop. Air fitting supplied (unless otherwise ordered) is for 8mm OD push in pipe.

BOUSSEY CONTROL EUROPE - Jacob Lacopstraat 36 Bus 101 - 9700 Oudenaarde - Belgium

☎ +32 55 423953 - 📠 + 32 55 612101

Email: info@boussey-control.eu – Site Internet: www.boussey-control.com

How it works

The Ionised Airgun consists of a hand trigger, air nozzle and an ionisation head engineered into the finger guard.

When the trigger is pulled air travels at high speed from the nozzle picking up the ionised air produced by the ionisation head.

The ionised air is blown at high speed towards the object. The ionisation kills the static electricity, allowing the dust to be blown off.

Both the object and the dust will be static-free so preventing re-attraction.

The 4125 requires clean and dry compressed air. The maximum recommended pressure is 5, though up to 7 Bar can be used.

Applications:

The 4125 is used to clean mouldings, plastic sheets, automobiles, electrical assemblies, displays, helicopters, jetfighter cockpits - wherever dust and static are a problem.

Manufactured without compromising performance and long life.

- **Maximum ionisation.**
The ions are produced outside of the gun resulting in a performance which is many times more effective than traditional designs.
- **Economical air consumption.**
The amplifier nozzle magnifies compressed air by up to 20:1.
- **Robust construction.**
Stainless steel ionisation tube. All major parts are replaceable.
- **Ergonomic.**
Four finger trigger minimises fatigue and repetitive strains.
- **Air Control.**
Design of trigger/valve gives operator control over airflow.
- **Hi-Flex cable.**
Designed for robot use.
- **High Thrust.**
For effective cleaning.



4125-T with top air inlet



4125-B with bottom air inlet

BOUSSEY CONTROL EUROPE - Jacob Lacopstraat 36 Bus 101 - 9700 Oudenaarde - Belgium

☎ +32 55 423953 - 📠 + 32 55 612101

Email: info@boussey-control.eu – Site Internet: www.boussey-control.com